

TECHNICAL DETAILS & ACCESSORIES



Housing

Material: hard anodised aluminium. No vent openings, service-friendly access to all interfaces.

Measurements		Weight	
21.5"	568 x 360 x 70 mm	21.5"	11.65 kg
32"	796 x 490 x 83 mm	32"	19.75 kg

Display & Buttons

TFT full HD active matrix (1920 x 1080 pixels)
 Brightness: 21.5" 250 cd/m² 32.0" 400 cd/m²

Capacitive multi-touch technology
Capacitive function buttons
 Can be operated with wet hands and light gloves

CPU	Intel® Atom E3845 quad core 1.91 GHz
Memory	2x4 GB DDR3L-SODIMM-1600
Hard Drive	32 GB mSATA
OS	Windows Embedded POSReady Windows 10 IoT

Interfaces

2 x USB 2.0 DP (DisplayPort) 2 x USB 2.0 on the rear
 Integrated switch: 4 Port Gbit Cold appliance socket 110 - 230 VAC

Power supply
 Integrated Power Supply 110 - 230 VAC

Certifications

- ✓ Safety requirement IEC 62368-1: 2014
- ✓ Protection class IP55 according to IEC 60529
- ✓ Interference emission according to EN61000-6-3:2007
- ✓ Interference stability according to EN61000-6-1:2007

Tested by external laboratories.

Special Features

- ✓ Automatic temperature monitoring
- ✓ Flashing LED signalling receipt of new ticket
- ✓ ‚Touch-lock‘ for cleaning device while in use
- ✓ Two stereo speakers with 3-watt output each

MOUNTING SYSTEMS

Table Mount
SF 215 / SF 320



Wall Mount
TAWH 400 215 / TAWH 400 320



Floor- & Ceiling-Mount

DBH 1200 215 DBH 1200 320
 height adjustable 120 cm - 150 cm

DBH 1600 215 DBH 1600 320
 height adjustable 140 cm - 190 cm

VESA adapter plate
 100 x 100 mm